



PRODUCT INFORMATION

Mod. R&S. 05/1

Pag. 1/1

Last Updating: 10/2008

COLORPRINT CRYSTAL MATT/GLOSSY

Description

Transparent Heat seal material, specifically formulated for ink jet solvent and eco solvent based inks – printing and cutting systems or thermoresin. The material is very thin, suitable for light coloured fabrics.

Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

Temperature: 160-165°C

Time: 15"

Pressure: medium

Application Instructions

- 1) **Before printing, remove the additional, external protective film (very easy to detach).**
- 2) **Print in reverse**, on the layer previously covered with the protective film and cut the material
- 3) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
- 4) Weed the exceeding material
- 5) Heat apply with its own polyester backing
- 6) Remove backing once **cold**

Suitable for

Cotton, polyester, poly-cotton blends.

Not suitable for treated and dyed garments (sublimation inks)

Washing: (wait 24h after the heat transfer)

50°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

Dry-cleaning : no

Tumble drier : no

N.B. : all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website www.siser.it.

For further information, please contact our Sales Office. Thank you.

SISER s.r.l.

V.LE DELLA TECNICA n. 18 – 36100 VICENZA ITALY

TEL. +39 0444 287960 - FAX +39 0444 287959 - E-mail: info@siser.it - www.siser.it

R.E.A. VI 171856 VI – Reg. Imp. VI n. 14971 - Cap. Soc. € 103.300 i.v. – Partita IVA 01591490246



Organizzazione con sistema di gestione certificato
ISO 9001:2008